

Fogging system
Fog module
air-water
max 2 nozzles



Detail of the electric connection suitable for air compressor module.



Detail of the pressure gauges to control air and water pressure.



Detail of the flow rate regulator.

Technical data

Code	Model	No. nozzles	Pressure	Flow rate	Power	Dimensions (W x L x H)	Weight
ZX.0614	ARIA ACQUA - 2	2	10 bar 145 psi	0,83 l/min 0.22 USGpm	200 W (1x230 V-50 Hz)	35 x 19 x 46 cm 13.8" x 7.25" x 18.2"	gr. 17500 oz. 618.0

Optional and accessories

LP.3150

gr. 5600
oz. 196.0

Polyethylene tank,
120 lt-31.70 USG capacity



AT.RLG1S2F3

gr. 120
oz. 4.2

Electric float N/O
(normally open) contact
640 mm-25.3"



ZX.0015

gr. 160
oz. 5.6

Air-water nozzle
G 1/4" F-F.
Made of:
stainless steel AISI 303 body,
Nicked brass air nozzle
and stainless steel AISI 303
water nozzle



Technical features

- **Frame** made of plastic sheet and painted cover.
- **Blade pump** 3 l/h-0.80 USGph
- **Electric motor**, single-phase, 110-230 V-50 Hz.
- **Air pressure regulator.**
- **Solution pressure regulator.**
- **Pressure gauge for air.**
- **Pressure gauge for solution.**
- **Electric board** complete with: general ON/OFF switch, transformer 220 / 24 V, relay, fuses. Warning indicators: electric board ON (WHITE), lack of air or solution (YELLOW).
- **Polyethylene tank**, 120 lt-31.70 USG.
- **Electric float**, 640 mm-25.3", N/O (normally open) contact.

IDROBASE®

PASSION FOR WATER 



idrobaser®

www.idrobaser.com



perfectcool®

www.perfectcool.it



idrotech®

www.idrotech.com



club dei riparatori®

www.sparesclub.com

35010 BORGORICCO (PD) ITALY -

Via dell'Industria, 25

Phone +39 049 9335903 - Fax +39 049 9335922

idrobase@idrobase.com

www.idrobasergroup.com

