

## Optional

### • Accessories

**LP.3150**

gr. 5600  
oz. 197.6

**Polyethylene tank**  
120 lt-31.70



**AT.RLG1S2F3**

gr. 120  
oz. 4.3

**Electric float N/O contact,**  
640 mm-25.2".



**CDR.0021**

gr. 360  
oz. 12.7

**Mechanical descaling device, G 1/2" M-F,**  
20 bar-290 psi,  
18 l/min-4.75 USGpm,  
100 °C-210 °F.



**J.RE4050212**

gr. 950  
oz. 33.6

**Anti-limescale and anti-corrosion dispenser**  
for domestic and industrial applications, with cartridge.  
Connection G1/2"  
1500 l/h



**J.MF8516000**

gr. 1015  
oz. 35.8

**Polyphosphate cartridge set (12 pcs),**  
for anti-limescale dispenser.



## Optional

### • Dosing pumps

**CDR.0351**

gr. 3100 / oz. 109.5

#### Electromagnetic analogue dosing pump

it is characterized by a high working frequency (400 imp/min).  
This solution allows a wide range of exact regulation and at the same time a uniform dosing.  
This pump has a constant flow rate with manual regulation from 0% to 100%.  
The ideal flow is obtained by a rotating knob under the front cover from 0% to 100%.  
All our pumps are IP65 protection with double insulation, which guarantees the maximum safety in compliance with CE rules.

#### Technical features

- Max flow rate 8 l/h-2.11 USGph
- Max pressure 8 bar-115 psi
- Power supply 230 V-50 Hz
- Power absorbed 55 VA
- Insulation class F

The pump includes: injection valve, foot filter, electric cable with plug and all you need to fix the pump to the wall.

**ZX.0911**

gr. 300  
oz. 10.5

**Connection kit for 60 bar fog module,**  
to connect dosing pump



**KDAR01**

gr. 1400 / oz. 49.4

#### Perfumed essence dosing pump

Is a simple yet reliable series of micro-processor based solenoid dosing pumps.

- External plastic enclosure in PP with IP65 protection degree protected against jets of water and aggressive environments
- Pump head with manual priming valve
- Flow rate manual adjustment from 0 (operation stop) to 100% of max. flow rate
- Standard 90-265 VAC power supply (20-60 VAC upon request)
- Pump can be equipped with low level alarm connection upon request

#### Technical features

- Max flow rate 2 l/h-0.52 USGph
- Max pressure 7 bar-100 psi
- Power supply 230 V-50/60 Hz



**DOS.D25RE2**

gr. 1700 / oz. 60.0

#### Dosing pump DOSATRON

Installed in the water system, Dosatron uses water pressure as the only driving force. Thus activated, Dosatron sucks out the concentrated product, doses it according to the needed percentage and then homogenizes it in the mixing chamber with the driving force water. The solution then flows out of the dispenser. The dose of the product is always proportional to the volume of water passing through Dosatron, regardless of flow rate and pressure.

#### Technical features

- Max flow rate 10 l/h-2.64 USGph
- Max pressure 0,3-6 bar / 4.5-87 psi
- Dosage percentage 0,1-0,9 %
- Power supply Water in pressure
- Connections G 3/4" M-M



# IDROBASE®

PASSION FOR WATER 



idrobaser®

[www.idrobaser.com](http://www.idrobaser.com)



perfectcool®

[www.perfectcool.it](http://www.perfectcool.it)



idrotech®

[www.idrotech.com](http://www.idrotech.com)



club dei riparatori®

[www.sparesclub.com](http://www.sparesclub.com)

35010 BORGORICCO (PD) ITALY -

Via dell'Industria, 25

Phone +39 049 9335903 - Fax +39 049 9335922

[idrobaser@idrobaser.com](mailto:idrobaser@idrobaser.com)

[www.idrobasergroup.com](http://www.idrobasergroup.com)

